

An efficient, cost-effective solution for outrigger support

Checkers outrigger crane pads are made from a special formulation high-quality polyethylene—they will not splinter or crack, are non-conductive, and will not absorb water. They provide a safe working environment for heavy equipment with outrigger arms. The unique design allows each pad to adapt to the working surface and return to its original shape once the work is complete.

The pads are strong and durable, easy to clean, and chemical and oil resistant. The lightweight design makes them easy to install and move around. Ideal for use in all weather conditions, the hard-wearing structure makes the pads unbreakable during normal working conditions.

- High load capacity designed to fully support vehicles and cranes without warping or splintering
- Engineered to bend but not break
- Recovery memory after bending restores original shape
- Safety textured surface and orange tough grip handles improve grip and stability



Model	Working Load Limit	Length	Width	Thickness	Weight
Medium-Duty Pads					
PAD1515.75	15,000 lbs (6,803 kg)	15 in (38.1 cm)	15 in (38.1 cm)	0.75 in (1.9 cm)	5.5 lb (3.4 kg)
PAD18181	45,000 lb (20,410 kg)	18 in (45.7 cm)	18 in (45.7 cm)	1 in (2.5 cm)	11 lb (5 kg)
PAD24241	60,000 lb (27,220 kg)	24 in (61 cm)	24 in (61 cm)	1 in (2.5 cm)	20 lb (9.1 kg)
PAD30301	75,000 lb (34,020 kg)	30 in (76.2 cm)	30 in (76.2 cm)	1 in (2.5 cm)	31 lb (14 kg)
PAD36361	80,000 lb (36,287 kg)	36 in (91.4 cm)	36 in (91.4 cm)	1 in (2.5 cm)	45 lb (20.4 kg)
PAD48481	80,000 lbs (36,287 kg)	48 in (122 cm)	48 in (122 cm)	1 in (2.5 cm)	80 lb (36.3 kg)
Heavy-Duty Pads					
PAD24242	80,000 lb (36,287 kg)	24 in (61 cm)	24 in (61 cm)	2 in (5 cm)	38 lb (17.2 kg)
PAD30302	95,000 lb (43,090 kg)	30 in (76.2 cm)	30 in (76.2 cm)	2 in (5 cm)	62 lb (28 kg)
PAD36362	110,000 lb (49,890 kg)	36 in (91.4 cm)	36 in (91.4 cm)	2 in (5 cm)	90 lb (40.8 kg)
PAD48482	140,000 lb (63,500 kg)	48 in (122 cm)	48 in (122 cm)	2 in (5 cm)	160 lb (72.6 kg)

