

---

# Replacement Rubber Pad for MC3012 Wheel Chocks - MCPAD20.25X2.5

## Product Images

---



## Short Description

---

- Lightweight with tough urethane construction
- Rated for vehicles with a gross operating weight up to 855,000 lbs., and tire sizes up to 142 in. diameter

- Maximum rated payload of 240 tons
- Resistant to oils, fuels, and solvents
- Approved and being used by Caterpillar and mines worldwide
- Optional studs available for snow and ice
- Barcode imprinted on back of chock
- ANSI compliant color guidelines on proper chocking and wheel chock placement in English
- Meets MSHA specifications
- Molded-in "How to Use" guidelines in English
- Safety yellow color
- Recessed carrying handle on the backside of the chock
- Replaceable rubber anti-slip traction pads
- Mounting hole for ropes, chains or brackets

## Description

---

Rubber replacement pad for use with MC3012 Wheel Chocks. The Checkers™ heavy-duty MC3009 wheel chocks for ground vehicles are manufactured with highly durable, lightweight polyurethane and they feature a larger base that makes them ideal for use with heavy equipment. MC3009 wheel chocks are designed for mine support equipment such as lubrication trucks and heavy maintenance vehicles. Rated for tire sizes up to 65 in. (165.1 cm) diameter and gross vehicle operating weight up to 245,000 lbs. (111,130 kg). A maximum rated payload of 70 tons.

## Specifications

---

Model No	MCPAD20.25X2.5
UPC	810043329200
Quantity Included	1
Length (Inches)	19.75
Width (Inches)	2
Height (Inches)	0.25

## Prop 65

---

**⚠️WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).